

# Technical Data Sheet



Product	Water-based Basecoats	
Codes	BWA1000-1999	Fine particle flake
	BWA2000-2999	medium particle flake
	BWA3000-3999	Coarse particle flake
	BWA4000-4999	Solid Colour
Use	As a colour coat between suitable primer and clear-coat.	
Mix	Paint is ready for use. Gently invert container before use. If container has been opened before then filter paint to ensure any dried paint flakes are removed.	
Preparation	Ensure all surfaces to be coated are dry and free from any grease and other contamination. Spray and dry primer as per manufacturer's instructions.	
Application	Allow substrate to warm to spraybooth temperature, typically 25 to 30°C. Spray with conventional spray equipment, typically 1.3mm fluid tip and 1.5 to 2 Bar pressure. Spray in two coats allowing the film to dry between coats, typically 5-10 mins depending on air temperature and air movement. Once sprayed, dry for 10-15 minutes in similar conditions. Apply clear-coat according to manufacturer's instructions.	
Notes	product is compatible with most clear-coats up to 200°C including 1K and 2K acrylics and polyesters.	
Health and Safety	Always read and understand the appropriate MSDS before proceeding	
storage	Store in cool dry cconditions in original packaging When not in use keep lids tightly closed	

Always check colour and finish before proceeding. Jaytees strive to ensure all information about the product is correct however we have no control over application conditions or equipment. Therefore we cannot accept liability for the performance of the product in service or any loss or damage arising out of use unless agreed in writing prior to use.

