

Technical Data Sheet



Product **Water-based Basecoats**

Codes **BWA1000-1999** Fine particle flake
BWA2000-2999 medium particle flake
BWA3000-3999 Coarse particle flake
BWA4000-4999 Solid Colour

Use As a colour coat between suitable primer and clear-coat.

Mix Paint is ready for use. Gently invert container before use. If container has been opened before then filter paint to ensure any dried paint flakes are removed.

Preparation Ensure all surfaces to be coated are dry and free from any grease and other contamination. Spray and dry primer as per manufacturer's instructions.

Application Allow substrate to warm to spraybooth temperature, typically 25 to 30°C. Spray with conventional spray equipment, typically 1.3mm fluid tip and 1.5 to 2 Bar pressure. Spray in two coats allowing the film to dry between coats, typically 5-10 mins depending on air temperature and air movement. Once sprayed, dry for 10-15 minutes in similar conditions. Apply clear-coat according to manufacturer's instructions.

Notes product is compatible with most clear-coats up to 200°C including 1K and 2K acrylics and polyesters.

Health and Safety Always read and understand the appropriate MSDS before proceeding

storage Store in cool dry cconditions in original packaging
When not in use keep lids tightly closed

Always check colour and finish before proceeding. Jaytees strive to ensure all information about the product is correct however we have no control over application conditions or equipment. Therefore we cannot accept liability for the performance of the product in service or any loss or damage arising out of use unless agreed in writing prior to use.

